

SPECIFICATIONS

2019 MULE PRO-FXT™ RANCH EDITION



POWER

Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Displacement	812cc
Maximum Torque	48.0 lb-ft @ 3500 rpm
Fuel System	DFI® with 34mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	75 amp

CAPABILITY

Steering	Electric Power Steering (EPS) / rack-and-pinion, (Non EPS rack-and-pinion)
Ground Clearance	10.2 in
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	42.7/22.0 x 53.7 x 11.0 in
Cargo Bed Capacity	1000 lb (3-person mode) 350 lb (6-person mode) (600 lb for California models)
Load Capacity	1616 lb
Seating Capacity	3-6
Towing Capacity	2000 lb
Lighting	(2) Halogen (high/low beam) headlights. Ranch Edition/LE/Camo models (2) additional auxiliary LED headlights (high/low beam)

DETAILS

Overall Length	133.3 in / 135.6 in (Ranch Edition)
Overall Width	64.0 in
Overall Height	79.5 in (Ranch Edition, EPS LE) / 77.6 (EPS, Camo, Non EPS)
Curb Weight	1962.5 lb (Ranch Edition) / 1922.8 (EPS LE) / 1911.7 (EPS) / 1916.1 (Camo) / 1887.5 (Non EPS)**
Wheelbase	92.3 in
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators (except Non EPS), neutral, reverse and parking indicators, seatbelt reminder lamps
Color Choices	Metallic Rustic Bronze
Warranty	Kawasaki Strong 3-Year Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24 or 36 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI.COM

Kawasaki